

Bond University
Research Repository



Barriers to building information modelling in the Chinese construction industry

Li, Hongyang; Thomas Ng, Shiu Tong; Skitmore, Martin; Zhang, Xiaoling; Jin, Zhigang

Published in:

Proceedings of the Institution of Civil Engineers: Municipal Engineer

DOI:

[10.1680/jmuen.16.00059](https://doi.org/10.1680/jmuen.16.00059)

Licence:

Other

[Link to output in Bond University research repository.](#)

Recommended citation(APA):

Li, H., Thomas Ng, S. T., Skitmore, M., Zhang, X., & Jin, Z. (2017). Barriers to building information modelling in the Chinese construction industry. *Proceedings of the Institution of Civil Engineers: Municipal Engineer*, 170(2), 105-115. <https://doi.org/10.1680/jmuen.16.00059>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

For more information, or if you believe that this document breaches copyright, please contact the Bond University research repository coordinator.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32

Paper for

**Proceedings of the Institution of Civil Engineers
Municipal Engineer**

Barriers to BIM in the Chinese AEC Industry

Hongyang Li^{1,2*}
*S. Thomas Ng*³
*Martin Skitmore*⁴
*Xiaoling Zhang*⁵
*Zhigang Jin*⁶

¹ Lecturer, School of Civil Engineering and Transportation, South China University of Technology, Guangzhou, PR China, 510640, Email: li.terryhy@yahoo.com (Corresponding author)

² State Key Laboratory of Subtropical Building Science, South China University of Technology, Guangzhou, PR China; 510640

³ Professor, Department of Civil Engineering, The University of Hong Kong, Pokfulam Road, Hong Kong, Email: tstng@hku.hk, Tel: Int+ (852) 2857 8556; Fax: Int+ (852) 2559 5337

⁴ Professor, School of Civil Engineering and Built Environment, Queensland University of Technology (QUT), Garden Point Campus, GPO Box 2434, Brisbane, Q4001, Australia, Email: rm.skitmore@qut.edu.au

⁵ Assistant Professor, Department of Public Policy, City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong; Shenzhen Research Institute, City University of Hong Kong, Shenzhen, China. Email: xiaoling.zhang@cityu.edu.hk

⁶ Associate professor, School of Construction Management and Real Estate, Chongqing University, Chongqing 400045, jinzg@cqu.edu.cn

Barriers to BIM in the Chinese AEC Industry

33
34
35
36

37 Abstract

38 The Chinese AEC (architecture, engineering and construction) industry is one of
39 the biggest and most important in the world, but also well known for its relatively low
40 efficiency and profitability. Building information modeling (BIM) has been introduced
41 as a concept to uplift the industry's efficiency and is becoming an increasingly popular
42 and a major topic in China, with strong commitment by the government for the
43 country's future national AEC development and mandatory adoption in some localities.
44 However, its take up in China continues to be very slow. The reasons for this have
45 received little systematic study to date. This paper describes a survey of 136 owners,
46 designers and contractors aimed at systematically and comprehensively analyzing the
47 barriers involved by examining and comparing the perceptions of these three
48 stakeholder groups.

49 The results indicate that owners have limited understanding of BIM except for its
50 3D visualization and clash detection capabilities, designers are predominantly
51 concerned with the uncertain amount of return of investment in the technology, and
52 contractors are worried about having to change their mode of operation. The conflicting
53 perceptions of BIM implementation barriers between the three groups arise mainly from
54 three sources: the drive for adoption, traditional culture and talent cultivation.
55 Specifically, key issues are the roles the government and the market should play in
56 assisting the BIM adoption and the importance of government mandates and incentives
57 given China's political, social, economic and cultural environment; the traditional
58 Chinese culture of encouraging thinking/doing in a more ambiguous manner than is
59 suited to BIM's emphasis on precision, with conventional management philosophy
60 paying more attention to people than technical development; and the need for qualified
61 BIM professionals capable of operating the software and managing construction as well
62 as coordinating team members.

63
64
65
66

Keywords: BIM, AEC industry, China, barriers, stakeholder survey.

67 1. Introduction

68 The Chinese AEC (architecture, engineering and construction) industry is one of
69 the biggest and most important markets around the world (Dodge Data & Analytics,
70 2015). However, its relatively low efficiency and profitability is a well-recognized
71 problem and practitioners are urged to adopt innovative technologies and processes to
72 improve the industry's overall performance. BIM (building information modeling) has
73 been introduced as a concept to uplift the industry's efficiency. Through BIM, building
74 information can be generated, stored, managed, exchanged and shared in an
75 interoperable and reusable manner (Eadie *et al.*, 2013). With overseas experience
76 demonstrating that great benefits can be obtained by the use of BIM in project delivery

77 (e.g. fewer design coordination errors, more energy efficient design solutions, faster
78 cost estimation, reduced production cycle times and lower construction costs)(Cao *et*
79 *al.*, 2015), BIM is becoming an increasingly popular and a major topic in China.

80 Commitment is strong, with BIM technology being seen by the government as
81 being crucial for national building industry development and with mandatory adoption
82 in some localities. However, despite this and there being little doubt that BIM will bring
83 a revolution to the industry, its take up in China continues to be very slow. The reasons
84 for this have received little systematic study to date. In response, this study aims to
85 systematically and comprehensively analyze the barriers to Chinese AEC industry BIM
86 adoption by examining and comparing the perceptions of the three main stakeholder
87 groups (owners, designers and contractors). The paper begins with a brief review of the
88 history of BIM and its application in China. This is followed by an introduction to the
89 research methodology and process. The survey results are then presented to uncover the
90 consistency and differences in the concerns of the groups regarding the obstacles to
91 BIM implementation in China together with the outcomes of a series of in-depth
92 validation interviews. Concluding remarks summarize the main findings and consider
93 the research agenda needed for the future.

94 **2. Literature review**

95 *2.1 BIM history and concept*

96 The concept of BIM, or building description systems more precisely, was first
97 developed by Eastman (1976) in the mid-1970s as “*a database capable of describing*
98 *buildings at a detail allowing design and construction*”. The ideas involved, i.e.
99 parametric design, deriving 2D drawings from a model, a “*single integrated database*
100 *for visual and quantitative analyses*” are beneficial for contractors of large projects in
101 terms of scheduling and materials ordering (Eastman, 1975). This method or approach
102 was later described as “building product models” in the United States or “product
103 information models” in Europe – both emphasizing “product” rather than “process”
104 (Eastman *et al.*, 2011). The term “building modeling” – which is closer to the term
105 “building information modeling” used today - was first documented in 1986, combining
106 the concepts of 3D modeling, automatic drawing extraction, intelligent parametric
107 components, relational databases, temporal phasing of construction processes, etc.
108 (Aish, 1986).

109 BIM, as an ever-evolving area and frontier, is creeping into the boundaries of its
110 concepts (RICS, 2014). Though difficult, many government departments of different
111 countries and regions and studies worldwide have provided exemplary definitions of
112 BIM, as summarized in Table 1.

113
114
115

<Insert Table 1>

116 A holistic definition of BIM should, therefore, encompass three interconnected
117 aspects, namely: the model product (i.e. a structured dataset describing a building),
118 modeling process (i.e. hardware and software used for creating a building information
119 model), and model application (i.e. collaborative practices, standards, semantics, etc.)
120 (Wong and Fan, 2013; RICS, 2014). The benefits of BIM are increasingly recognized
121 by practitioners and academics, with its application providing up to 40% reduction in
122 unbudgeted changes; cost estimation accuracy within 3% as compared to traditional

123 estimates; up to 80% reduction in time taken to generate a cost estimate; savings of up
124 to 10% of the contract value through clash detections; and up to 7% reduction in project
125 time (Azhar, 2011).

126 The benefits of BIM also differ between different project stakeholder groups
127 (McGraw Hill Construction, 2014a; 2014b). The most important three advantages of
128 BIM engagement, as rated by contractors for example, comprise reduced errors and
129 omissions, collaboration with owners / design firms and an enhanced organizational
130 image (McGraw Hill Construction, 2014a). Owners, on the other hand, perceive
131 visualization as the top BIM benefit since it enables the proposed design to be better
132 understood (McGraw Hill Construction, 2014b). As a result, many researchers are
133 advocating the application of BIM at all stages of the project life-cycle (Eadie *et al.*,
134 2013; Bryde *et al.*, 2013), with the Singapore Building and Construction Authority, for
135 example, detailing the BIM key activities and objectives involved in each project phase
136 of conceptual design, schematic/preliminary design, detailed design, construction, as-
137 built and facility management (BCA, 2013).

138

139 *2.2 BIM adoption in the Chinese AEC industry*

140 The United States and Scandinavian region (i.e. Norway, Denmark and Finland)
141 have long been the global leaders in BIM implementation in the AEC industry (Smith,
142 2014). China, however, is still in the infancy stage of BIM adoption. A very recent study
143 conducted by Dodge Data & Analytics found that, nearly half (46%) of the architects
144 and a third (31%) of the contractors in China are currently at the lowest level of BIM
145 implementation (i.e. less than 15% of projects involving the use of BIM) (Dodge Data
146 & Analytics, 2015). Nevertheless, the commitment of the AEC industry in China to
147 adopt BIM is strong. This is partly attributed to the national / provincial requirements
148 for innovation and development. As emphasized in the Ministry of Housing and Urban-
149 Rural Development's 12th national 5-Year Plan, BIM technology is crucial for
150 developing the national building industry in terms of industrialization, informatization,
151 urbanization and agricultural modernization. In Guangdong province, BIM adoption is
152 generally required for all projects with building area no less than 20,000 m² by the end
153 of 2020 (Department of Housing and Urban-Rural Development of Guangdong
154 Province, 2014). Although Chinese AEC industry practitioners have a powerful
155 demand for BIM, both actively and passively, its implementation in the country is not
156 easy. Various barriers have hindered BIM development to date and a thorough
157 identification of these is a timely and valuable need for improving BIM practices and
158 the effectiveness of the industry.

159 **3. Research methodology and process**

160 A combination of common construction management research methods was
161 adopted in this study, comprising (i) literature review; (ii) interviews; and (iii)
162 questionnaire survey to thoroughly and comprehensively collect data concerning BIM
163 application both locally and outside China.

164

165 *3.1 Literature Review*

166 The global literature was carefully reviewed and analyzed through content analysis.
167 As a result, the barriers to BIM application in the AEC Industry in different countries
168 and regions identified as summarized in Table 2.

169
170 <Insert Table 2>

171
172 *3.2 Interviews*

173 The findings of the literature review served as the basis for compiling a list of
174 barriers to BIM implementation on the international scale. Their applicability in the
175 Chinese context was then tested through a pilot study involving 11 experts from various
176 stakeholder groups in the China AEC industry. At the final stage of the research, a series
177 of semi-structured interviews were conducted to confirm the validity of survey findings.
178 To facilitate and expedite the interview process, all the interviewees were provided with
179 a package of information in advance that included the purpose of the interview,
180 background information, instructions for the exercise and a brief description of the
181 current survey findings. The interviewees were all purposively selected based on their
182 theoretical knowledge of, and practical experience in, BIM adoption in the Chinese
183 AEC industry. To qualify, the interviewees were required to have a minimum of five
184 years of working or research experience in BIM-related disciplines or have previously
185 been involved in the application of BIM for at least two projects in China. Table 3
186 provides the profiles of the participants, indicating that all interviewees have ample
187 hands-on BIM experience and therefore sufficiently knowledgeable for their opinions
188 to be credible enough for the research.

189
190 <Insert Table 3>

191
192 *3.3 Questionnaire Survey*

193 A draft questionnaire was designed from the results of the literature review and
194 piloted with the 11 interviewees profiled in Table 3 to ensure the questions were
195 intelligible, easy to answer, unambiguous and short enough to be completed within time
196 required. As a result, 12 barriers hindering BIM adoption in the AEC industry were
197 identified (Table 4). A 5-point Likert scale is used to solicit comments from the owner,
198 designer and contractor stakeholder groups regarding the relative importance of each
199 barrier. To improve the reliability of survey findings, all respondents from the three
200 groups were selected on a purposive basis, with the requirement to have a minimum of
201 two years of working or research experience in BIM-related disciplines or have
202 previously been involved in BIM application in at least one project in China.

203
204 <Insert Table 4>

205
206 A total of 555 questionnaires were dispatched and 136 were returned by post, email
207 or fax (Table 5), representing a response rate of 24.5%. This response rate is common
208 for a survey of this kind and is regarded as acceptable based on the findings of Akintoye
209 (2000).

210
211 <Insert Table 5>

212 4. Data analysis and results

213 Various analytical techniques were adopted, including the mean score ranking
214 technique, independent sample *t*-tests and ANOVA. As a result, the relative importance
215 of the different BIM adoption obstacles as perceived by each stakeholder group was
216 ranked and any significant perceptual differences identified. The comments raised by
217 the interviewees during the validation interviews were also recorded.

218 4.1 Ranked barriers of BIM adoption

220 Chan *et al.* (2009) apply the mean score ranking technique to delineate the
221 importance of different drivers for the adoption of public private partnerships. Using
222 the same technique, the data collected from the questionnaire was analyzed according
223 to the statistic:

$$224 \text{ Mean Score} = \frac{\sum(f \times s)}{N}, (1 \leq \text{Mean Score} \leq 5) \quad (1)$$

225 where *s* represents the score of each barrier ranging from 1 (least important) to 5 (most
226 important); *f* stands for the frequency of response to each rating (1-5) for each barrier;
227 and *N* denotes the total number of responses concerning a specific barrier.

228 Based on the responses obtained from the three stakeholder groups, the mean of
229 each BIM application obstacle were calculated and ranked as shown in Table 4 with the
230 scale intervals being: (i) “not important” (mean score ≤ 1.5); (ii) “fairly important”
231 ($1.51 \leq \text{mean score} \leq 2.5$); (iii) “important” ($2.51 \leq \text{mean score} \leq 3.5$); (iv) “very
232 important” ($3.51 \leq \text{mean score} \leq 4.5$); and (v) “extremely important” (mean score \geq
233 4.51).

235 4.1.1. Concerns of owners

236
237 The owner representatives give comparatively higher mean scores to majority of
238 the factors (Table 4), with F1 - lack of understanding (4.74); F7 – not sure if the benefits
239 outweigh the costs when implementing BIM (4.72); and F11 - insufficient government
240 lead/direction (4.62) being their top concerns. These results are confirmed by the
241 validation interviews, with five of the six owner interviewees admitting that, although
242 having heard of BIM, their understanding of the concept is still very superficial. The
243 academic contingent further pointed out that a considerable number of Chinese owners
244 simply consider BIM as 3D visualization and that its benefits only arise in clash
245 detection. As a result, they invest prudently in BIM. As commented by two owner
246 interviewees, “We still doubt whether the benefits can outweigh the costs when
247 implementing BIM. Instead, we would rather trust the existing mature technology”.

249 4.1.2. Concerns of designers

250
251 Two factors, including F7 – not sure if the benefits outweigh the costs when
252 implementing BIM; and F2 – lack of owner demand) are rated by designers as
253 “extremely important”. All the five designer representatives agree that the initial
254 investment in hardware and software for BIM adoption could place heavy financial
255 burdens on the design companies/institutes. The three academic representatives also
256 believe that human capital is insufficient in the current competitive environment and it
257 is costly to train qualified staff. On the other hand, two designers find that the
258 competitive edge of the design companies/institutes with BIM skills (especially those

259 medium and small-sized) is probably not decisive in winning projects when contending
260 with large design enterprises. Instead, owners without BIM requirements are lured away.
261

262 4.1.3. Concerns of contractors 263

264 As revealed from the questionnaire results, the contractors identify F12 -
265 resistance to change of culture/thinking mode (4.86); F7 – not sure if the benefits
266 outweigh the costs when implementing BIM (4.71); and F3 – lack of experienced BIM
267 professionals (4.51) as extremely important barriers, with two contractor interviewees
268 complaining that “involving BIM in the construction process has disrupted our
269 traditional workflow”. The academics explained that it takes time to change from an
270 extensive to intensive management mode and this process, to some extent, conflicts
271 with the benefits of traditional contractors in China. Their comments that “the increased
272 transparency through BIM application may reduce the chances of contractors obtaining
273 extra income from quantity overruns” further illustrate the point.
274

275 4.2 Disparity of perceptions between paired stakeholder groups

276 Independent sample *t*-tests were used to identify any significant differences in the
277 mean scores of the paired groups in relation to their perspectives, with $p < 0.05$ (two-
278 tailed) as the cut-off value (Table 6). Levene’s test was also conducted to determine if
279 the variances between the pairs of groups could be assumed to be homogeneous, again
280 with $p < 0.05$ as the cut-off value.
281

282 <Insert Table 6>
283
284

285 4.2.1 Owner vs. designer 286

287 According to Table 6, five factors vary considerably between the owner and
288 designer groups. These comprise F2 – a lack of owner/contractor demand (*mean*
289 *difference*=-1.14947); F11 – insufficient government lead/direction (*mean*
290 *difference*=0.59202); F8 – increased workload and decreased efficiency (*mean*
291 *difference*=-0.42553); F1 – lack of understanding (*mean difference*=0.41968); and F3 -
292 lack of experienced BIM professionals (*mean difference*=0.36915). Most of the
293 designer group interviewees find that, in addition to the extra cost of hardware/software,
294 adopting BIM may also lead to an increased workload when compared with the
295 traditional design process due to the incorporation of the whole-life cycle concept. As
296 a design director complained, “we have to think from a whole-life cycle perspective
297 rather than merely focusing on the design itself. The decreased efficiency may cause
298 delay in the design period”. As a result, design companies/institutes lack the impetus
299 to actively embrace BIM unless there is a strong driver from the owner. Three research
300 institutions/universities interviewees further added that it is reasonable for the owner to
301 play the leading role in promoting BIM implementation since they stand to gain the
302 most from the process. The owner representatives, on the other hand, admitted that most
303 of them are relatively conservative in BIM implementation and urged for stronger
304 support from the government in terms of policy, mandates and incentives.
305

306 4.2.2 Owner vs. contractor 307

308 Comparing the results of the owner and contractor groups, significant differences
309 in the scores occur in six concern factors (Table 6), with F12 – resistance to change of
310 culture/thinking being the greatest (*mean difference*=-0.68693). It is surprising to note
311 that the vast majority of owners (5 out of 6 involved in the validation interviewees) had
312 an open mind and were willing to make a difference in terms of management mode.
313 After all, the ambiguous attitude towards the thinking/doing nexus is long and deep-
314 rooted in the populace’s mind. Still, two owner representatives reminded that the
315 “return of investment (ROI) in BIM remains in question in China since convincing
316 successful cases are normally only from overseas”. The government side responded that
317 increasing numbers of pilot BIM projects will be launched in various cities in China in
318 future to guide BIM application in the AEC industry. Greater resistance was expected
319 from the contractor group since the BIM concepts, such as precision, transparency, etc.,
320 are contrary to their traditional working mode, and especially the way they can earn
321 extra profits.
322

323 4.2.3 Designer vs. contractor 324

325 As Table 6 reveals, the designers disagree with the contractors on four concern
326 factors, the most important being F3 – lack of experienced BIM professionals (*mean*
327 *difference*=-0.56020). Four contractors stated that, although BIM requires design
328 professionals to change their mindset from the conventional 2D to 3D, representation
329 the accessibility of relevant software has made this process much easier. On the other
330 hand, they emphasized that in addition to technical abilities, qualified BIM staff in
331 construction companies should be equipped with detailed knowledge of construction
332 management and be strongly capable coordinators. However, as a chief engineer of a
333 construction company pointed out, “*such adequately trained/experienced professionals*
334 *are rather scarce*”. The academics admitted that “*very few universities in China have*
335 *incorporated BIM into the current curriculum system of either undergraduate and*
336 *postgraduate studies as compared with overseas teaching/learning*”. They are still keen
337 for talent to be cultivated, however, since market demand is ever growing.
338

339 4.3 Disparity of perceptions among the three stakeholder groups

340 One-way ANOVA was used to comprehensively compare the three stakeholder
341 groups. The results are summarized in Table 7. The mean ratings of the concern factors
342 F2 – lack of owner demand (*F* value=24.009), F12 – resistance to change of
343 culture/thinking mode (*F* value=15.920); and F1 – lack of understanding (*F*
344 value=13.890) emerge as the top three conflicts of the three groups. While the designers
345 attribute the current relatively low level of BIM adoption to insufficient owner drivers,
346 the owners again emphasize the important role of government in overcoming the barrier.
347 As a deputy general manager of a real estate corporation stated, a large number of
348 owners in China are conservative (or shortsighted to some extent) and they are currently
349 not willing to risk money in promoting a novel technique such as BIM. Government’s
350 policies, mandates and incentives could be a solution.

351 The academics further added that support from the government could help the
352 owner take the first step so that they can progressively realize the benefits obtained
353 from BIM adoption. As explained by a deputy director of a provincial research
354 institution, “After all, the largest contribution will go to their side as compared with
355 designers or contractors”. The contractor representatives, however, find the largest
356 barrier to BIM application not to be the insufficient drive of the owners or government,

357 but that adopting BIM may completely change the unique way in which Chinese
358 contractors normally operate, and hence the resistance is expected to remain. On the
359 other hand, the owners and designers are more willing to change even with the
360 temporary increased workload and decreased efficiency. As commented by the owner
361 and designer representatives "... we need to confirm the benefits outweigh the costs
362 when implementing BIM in the first place". The level of understanding of BIM varies
363 between the three stakeholder groups and the fact that owners have the least
364 understanding is expected. A university professor explained that this phenomenon
365 corresponds with the traditional Chinese management philosophy, which concentrates
366 more on people than technique – commenting that "Improving top management's
367 recognition of BIM will facilitate its promotion. It works for all the three parties
368 considered".
369

<Insert Table 7>

371 **5. Conclusions**

372 This paper has ranked the relative importance of BIM adoption obstacles in the
373 Chinese AEC industry as perceived by the owner, designer and contractor groups. The
374 owners' understanding of BIM is rather limited and normally is very much related to
375 3D visualization and clash detection. The designers, on the other hand, attribute the
376 current low level of BIM use to the questionable amount of return of investment in the
377 technology and process. From the perspective of the contractors, having to change their
378 mode of operation appears to be the biggest obstacle involved.

379 Conflicting perceptions of BIM implementation barriers were also observed
380 between paired stakeholder groups and generally. These conflicts arise from three
381 aspects: (i) drive for adoption; (ii) the traditional culture; and (iii) talent cultivation. A
382 consensus was easily reached among the validation interviewees that owners, as the
383 biggest beneficiary, should bear the greatest responsibility for promoting BIM, with a
384 key issue being the roles the government and the market should play in assisting the
385 process. Under current circumstances, government mandates and incentives seem more
386 useful given the political-social-economic-cultural environment in China. Traditional
387 Chinese culture encourages thinking/doing in a more ambiguous manner that violates
388 BIM's emphasis on precision. While owners and designers may embrace the change
389 involved and that the use of BIM can lead to a reasonable return on investment, the
390 resistance of contractors seems inevitable and rather difficult to address. After all, they
391 stand to suffer the most since the way they previously earned extra profits would no
392 longer be possible. The conventional management philosophy in China pays more
393 attention to people, with technique being relatively less important. This has led to an
394 insufficient understanding of BIM among senior management and especially owners.
395 Educating decision-makers is therefore likely to be a positive and effective method to
396 facilitate increased BIM use. Talent cultivation, on the other hand, involves far more
397 than just deepening the knowledge of senior management. It requires qualified BIM
398 professionals to be capable of operating the software and managing construction as well
399 as coordinating team members. In this regard, research institutions/universities in China
400 still have a long road to travel. For the next step, more effort needs to be directed at
401 identifying and implementing other possible means of removing the barriers to BIM
402 adoption, through which a framework can be established to fully exploit this
403 revolutionary technology in the Chinese AEC industry in future.

404 **Acknowledgments**

405 This project is funded by National Natural Science Foundation of China (Grant No.
406 71501074), the State Key Lab of Subtropical Building Science, South China University
407 of Technology, China (Grant No. 2016ZB16) and the Fundamental Research Funds for
408 the Central Universities (Approval No. 2015BS11; Project No. x2tj/D215315w).

409 **References**

410 A. Akintoye, Analysis of factors influencing project cost estimating practice,
411 Construction Management & Economics 18 (1) (2000) 77-89.

412
413 A.P. Chan, P.T. Lam, D.W. Chan, E. Cheung, Y. Ke, Drivers for adopting public private
414 partnerships—empirical comparison between China and Hong Kong special
415 administrative region, Journal of Construction Engineering and Management 135 (11)
416 (2009) 1115-1124.

417
418 Bips, 3D Working Method 2006, Denmark, 2007.

419
420 Building and Construction Authority, Singapore BIM Guide (Version 2), BCA,
421 Singapore, 2013.

422
423 Building Information Modelling Task Group, What is BIM? UK, 2013.

424
425 C. Eastman, General purpose building description systems, Computer-Aided Design 8
426 (1) (1976) 17-26.

427
428 C.M. Eastman, The use of computers instead of drawings in building design, AIA
429 Journal 63 (3) (1975) 46-50.

430
431 C. Eastman, P. Teicholz, R. Sacks, K. Liston, BIM handbook: A guide to building
432 information modeling for owners, managers, designers, engineers and contractors, John
433 Wiley & Sons, New Jersey, 2011.

434
435 C.T.W. Chan, Barriers of implementing BIM in construction industry from the
436 designers' perspective: A Hong Kong experience, Journal of System and Management
437 Sciences 4 (2) (2014) 24-40.

438
439 D. Bryde, M. Broquetas, J.M. Volm, The project benefits of building information
440 modelling (BIM), International Journal of Project Management 31 (7) (2013) 971-980.

441
442 D. Cao, G. Wang, H. Li, M. Skitmore, T. Huang, W. Zhang, Practices and effectiveness
443 of building information modelling in construction projects in China, Automation in
444 Construction 49 (2015) 113-122.

445
446 Department of Design and Construction, BIM Guidelines, New York City, USA, 2012.

447
448 Department of Housing and Urban-Rural Development of Guangdong Province,
449 Application of BIM technology, Guangzhou, China, 2014.

450
451 Department of Veterans Affairs, The VA BIM Guide, USA, 2010.
452
453 Dodge Data & Analytics, The Business Value of BIM in China, MA, USA, 2015.
454 F. Khosrowshahi, Y. Arayici, Roadmap for implementation of BIM in the UK
455 construction industry, *Engineering, Construction and Architectural Management* 19 (6)
456 (2012) 610-635.
457
458 General Services Administration, BIM Guide Overview, GSA, USA, 2007.
459
460 Hong Kong Institute of Building Information Modelling, BIM Project Specification,
461 Hong Kong, 2011.
462
463 I.A.R. Aftab Hameed Memon, Irfana Memon, Nur Iffah Aqilah Azman, BIM in
464 Malaysian Construction Industry: Status, Advantages, Barriers and Strategies to
465 Enhance the Implementation Level, *Research Journal of Applied Sciences, Engineering*
466 *and Technology* 8 (5) (2014) 606-614.
467
468 I. Kiani, A.N. Sadeghifam, S.K. Ghomi, A.K.B. Marsono, Barriers to Implementation
469 of Building Information Modeling in Scheduling and Planning Phase in Iran, *Australian*
470 *Journal of Basic and Applied Sciences* 9 (5) (2015) 91-97.
471
472 K.D. Wong, Q. Fan, Building information modelling (BIM) for sustainable building
473 design, *Facilities* 31 (3/4) (2013) 138-157.
474
475 K. Newton, N. Chileshe, Enablers and Barriers of Building Information Modelling
476 (BIM) within South Australian Construction Organisations, University of New South
477 Wales, 2012.
478
479 M. Abubakar, Y. Ibrahim, D. Kado, K. Bala, Contractors' perception of the factors
480 affecting building information modelling (BIM) adoption in the Nigerian construction
481 industry, *Computing in Civil and Building Engineering* (2014), ASCE, pp. 167-178.
482
483 McGraw Hill Construction, The Business Value of BIM for Construction in Major
484 Global Markets: How Contractors Around the World Are Driving Innovation With
485 Building Information Modeling, MA, USA, 2014a.
486 McGraw Hill Construction, The Business Value of BIM for Owners, MA, USA, 2014b.
487
488 Ministry of the Interior and Kingdom Relations, Rgd BIM Standard, the Netherlands,
489 2012.
490
491 National BIM Standards Committee, National BIM standard: version 2, NBIMS, USA,
492 2014.
493
494 National Institute of Building Sciences, National Building Information Modeling
495 Standard, NIBS, USA, 2007.
496
497 P. Smith, BIM Implementation–Global Strategies, *Procedia Engineering* 85 (2014)
498 482-492.
499

500 R. Aish, Building Modelling: The key to integrated construction CAD, CIB 5th
501 International Symposium on the Use of Computers for Environmental Engineering
502 Related to Buildings, 7-9 July, 1986.
503

504 R. Eadie, M. Browne, H. Odeyinka, C. McKeown, S. McNiff, BIM implementation
505 throughout the UK construction project lifecycle: An analysis, Automation in
506 Construction 36 (2013) 145-151.
507

508 Royal Institution of Chartered Surveyors, International BIM implementation guide (1st
509 edition), RICS, UK, 2014.
510

511 R. Stanley, D. Thurnell, The benefits of, and barriers to, implementation of 5D BIM for
512 quantity surveying in New Zealand, 2014.
513

514 S. Azhar, Building information modeling (BIM): Trends, benefits, risks, and challenges
515 for the AEC industry, Leadership and Management in Engineering (2011).
516

517 The AEC (UK) committee, AEC (UK) BIM Standard, UK, 2009.
518 The Associated General Contractors of America, The Contractor's Guide to BIM (2nd
519 edition), AGC, USA, 2010.
520

521 The British Standards Institution, Building information modelling - Information
522 delivery manual: Part 1: Methodology and format, BSI, UK, 2010.
523
524

Table 1: The BIM Definitions

Country/region	BIM definition	Reference
USA	<i>‘A BIM is a digital representation of the physical and functional characteristics of a facility. As such it serves as a shared knowledge resource for information about a facility, forming a reliable basis for decisions during its lifecycle from inception onward.’</i>	NIBS, 2007
	<i>‘Building Information Modeling is the development and use of a multi-faceted computer software data model to not only document a building design, but to simulate the construction and operation of a new capital facility or a recapitalized (modernized) facility. The resulting Building Information Model is a data-rich, object-based, intelligent and parametric digital representation of the facility, from which views appropriate to various users’ needs can be extracted and analyzed to generate feedback and improvement of the facility design.’</i>	GSA, 2007
	<i>‘A collection of defined model uses, workflows, and modeling methods used to achieve specific, repeatable and reliable information results from the model. Modeling methods affect the quality of the information generated from the model. When and why a model is used and shared, impacts the effective and efficient use of BIM for desired project outcomes and decision support.’</i>	DVA, 2010
	<i>‘An electronic representation of a facility for the purpose of design, analysis, construction and operation. A BIM consists of geometric, 3D representations of the building elements plus additional information that needs to be captured and transferred in the AEC delivery process and in the operations process of a facility.’</i>	AGC, 2010
	<i>‘Building Information Modeling (BIM) refers to a digital collection of software applications designed to facilitate coordination and project collaboration. BIM can also be considered as a process for developing design and construction documentation by virtually constructing the building on the computer before actually building it.’</i>	DDC, 2012
	<i>‘Building Information Modelling is digital representation of physical and functional characteristics of a facility, creating a shared knowledge resource for information about it and forming a reliable basis for decisions during its life cycle, from earliest conception to demolition.’</i>	NBIMS, 2014
	<i>‘BIM is one of the most promising developments that allows the creation of one or more accurate virtual digitally-constructed models of a building to support design, construction, fabrication, and procurement activities through which the building is realized.’</i>	Eastman et al., 2011

UK	<i>‘The effective collection and reuse of project data in order to reduce errors and increase focus on design and value.’</i>	AEC, 2009
	<i>‘A shared digital representation of the physical and functional characteristics of any built object (including buildings, bridges, roads, etc.) that forms a reliable basis for decisions.’</i>	BSI, 2010
	<i>‘BIM is essentially value creating collaboration through the entire life-cycle of an asset, underpinned by the creation, collation and exchange of shared 3D models and intelligent, structured data attached to them.’</i>	BIM Task Group, 2013
Denmark	<i>‘A method that is based on a building model containing any information about the construction. In addition to the contents of the 3D object-based models, this is information such as specifications, building element specifications, economy and programmes.’</i>	Bips, 2007
	<i>‘A modelling concept in which all parties create and use consistent digital information throughout the life of a construction project. This involves not only CAD and object data, but also any information relating to a project, such as detailed solutions, specifications and project documentation such as minutes of meetings etc.’</i>	
The Netherlands	<i>‘The integral 3D information source model of the building as constructed with BIM objects in a BIM modelling application. The BIM may consist of multiple individual models, for instance for separation per discipline or aspect. The BIM contains all building information necessary for the production of the required BIM extracts.’</i>	MIKR, 2012
Hong Kong	<i>‘The process of generating and managing building data during its life cycle. Typically, it uses three-dimensional, real-time, dynamic building modelling software to increase productivity in building design and construction. The process produces the Building Information Model (also abbreviated BIM), which encompasses building geometry, spatial relationships, geographic information, and quantities and properties of building components.’</i>	Hong Kong Institute of BIM, 2011

Table 2: Barriers to BIM application in the AEC industry in different countries and regions.

Countries and regions	Barriers to BIM application in the AEC industry
UK (Khosrowshahi and Arayici, 2012)	<ol style="list-style-type: none"> 1) Firms are not familiar enough with BIM use 2) Reluctance to initiate new workflows or train staff 3) Benefits of implementation do not outweigh the costs of implementation 4) Benefits are not tangible enough to warrant its use 5) Does not offer enough financial gain to warrant its use 6) Lacks the capital to invest in the hardware and software involved 7) Too risky from a liability standpoint to warrant its use 8) Resistance to a change in culture 9) No demand for its use
Australia (Newton and Chileshe, 2012)	<ol style="list-style-type: none"> 1) Lack of understanding 2) Education and training costs 3) Start-up costs 4) Changing the ways firms do business 5) Finding trained staff 6) Administrative costs 7) Collaboration between disciplines 8) Sharing information 9) Data ownership 10) Interoperability between models
New Zealand (Stanley and Thurnell, 2014)	<ol style="list-style-type: none"> 1) Lack of software compatibility restricts its use 2) The setup cost inhibits its use i.e. software, training and hardware costs 3) Increased risk exposure discourages companies e.g. legal issues such as ownership of BIM models 4) Cultural resistance in companies hinders its effectiveness 5) Incompatibility with industry-recognized element formats for cost planning prevents companies from adopting the software 6) Incompatibility with current Standard Methods of Measurement 7) Lack of integration in the model decreases the reliability and effectiveness of 5D (3D plus time and cost) (e.g. Arch./Eng./MEP designers are not all working off the same model) 8) Lack of protocols for coding objects within BIM models by designers hinder the development of cost modeling using BIM (e.g. lack of complete specification information in BIM models inhibits accurate quantity generation for estimating) 9) Some companies feel their current software meets their needs, so see no need to change 10) The fragmented nature of the construction industry limits its potential 11) Lack of an electronic standard for coding BIM software to Standard Methods of Measurement limits the potential of BIM for cost modeling
Malaysia (Memon <i>et al.</i> , 2014)	<ol style="list-style-type: none"> 1) Lack of competent staff to operate the software 2) Unawareness of the technology 3) Non availability of a parametric library 4) Expensive software 5) Not ready to distort the normal operational structure 6) Takes longer time to develop the model 7) Difficult to learn 8) No enforcement from owner
Iran (Kiani <i>et al.</i> , 2015)	<ol style="list-style-type: none"> 1) Lack of legal backing from authority 2) Lack of skilled BIM software operators 3) High price of software 4) Benefits of using BIM-based scheduling and planning are not tangible 5) Not required by owners

	6) Takes longer time to develop a schedule
	7) Request by other team members
	8) Costly hardware
	9) Request by owner in limited phases of projects
	10) Learning difficulty of BIM tools
	11) Request by owner in phase of construction
	12) Availability of drawings and specifications in the design phase
	13) No need to change conventional methods
	14) CPMs resistance to change
	15) Availability of teaching aids of BIM-based scheduling
	16) Availability of related courses in universities
Hong Kong (Chan, 2014)	1) Lack of qualified in-house staff to carry out the BIM related works
	2) Lack of training/education
	3) Lack of standards
	4) Lack of owner demand
	5) Lack of government lead/direction
	6) Lack of incentive to have subcontractors and suppliers (lower part of the supply chain) adopt BIM
	7) High cost
	8) Uncertainties over interoperability of BIM software with other software
	9) Lack of IT infrastructure
	10) Uncertainties over ownership of data and responsibilities
	11) Lack of new and/or amended forms of construction contracts
	12) Current professional indemnity and insurance terms
Nigeria (Abubakar <i>et al.</i> , 2014)	1) Social and habitual resistance to change
	2) Legal and contractual constraints
	3) High cost of training
	4) Lack of enabling environment (government policies and legislations)
	5) Lack of trained professionals to handle the tools
	6) Owners not requesting the use of BIM on projects
	7) No proof of financial benefits
	8) High cost of integrated software/models for all professionals
	9) Lack of standards to guide implementation
	10) Poor internet connectivity
	11) Frequent power failure
	12) Lack of awareness of the technology among industry stakeholders

Table 3: The Profiles of the Interviewees

Group	No.	Position	Organization	Research Stage Involved	
				Pilot Study	Validation
Owner	1	Project Manager	Real Estate Corporation	✓	
	2	Senior Consultant	Investment Corporation	✓	
	3	Quantity Surveyor	Real Estate Corporation	✓	
	V1	Engineering Manager	Real Estate Corporation		✓
	V2	Deputy General Manager	Real Estate Corporation		✓
	V3	Technical Director	Railway Company		✓
	V4	Chief Engineer	Real Estate Corporation		✓
Designer	V5	Deputy General Manager	Subway Construction Office		✓
	V6	Civil Engineer	Real Estate Corporation		✓
	4	Senior Architect	Design Consultants	✓	
	5	Chief Engineer	Design Institute	✓	
	V7	Vice President	Design Institute		✓
	V8	Technical Director	Design Company		✓
Contractor	V9	Associate Architect	Design Institute		✓
	V10	Chief Planner	Design Company		✓
	V11	Design Director	Design Institute		✓
	6	Deputy General Manager	Construction Company	✓	
Government Department	7	Engineering Manager	Construction Company	✓	
	V12	Chief Engineer	Construction Company		✓
	V13	Technical Manager	Construction Company		✓
	V14	Deputy Engineering Manager	Construction Company		✓
	V15	Project Manager	Construction Company		✓
	V16	Deputy Technical Manager	Construction Company		✓
Research Institution/University	8	Policy Advisor	Provincial Department	✓	
	9	Deputy Director	Municipal Department	✓	
	V17	Deputy Director	Provincial Department		✓
	V18	Director	Municipal Department		✓
	V19	Deputy Director	Provincial Department		✓
	V20	Deputy Secretary-general	Municipal Department		✓
Research Institution/University	V21	Deputy Director	Municipal Department		✓
	10	Deputy Director	National Research Institution	✓	
	11	Professor	University	✓	
	V22	Senior Research Fellow	University		✓
	V23	Associate Professor	University		✓
	V24	Deputy Director	Provincial Research Institution		✓
Research Institution/University	V25	Associate Research Fellow	Provincial Research Institution		✓
	V26	Professor	University		✓

Table 4: Perceptions of Various Stakeholder Groups regarding the Barriers of BIM Adoption in the AEC Industry in China

No.	Barriers of BIM Adoption in the Chinese AEC Industry	Stakeholder Group							
		Owner		Designer		Contractor		Overall	
		Mean Score	Ranking	Mean Score	Ranking	Mean Score	Ranking	Mean Score	Ranking
F1	Lack of understanding	4.74	1	4.33	4	4.08	9	4.38	4
F2	Lack of owner demand	3.43	12	4.58	2	4.06	11	3.99	9
F3	Lack of experienced BIM professionals	4.32	6	3.95	10	4.51	3	4.28	7
F4	High costs of education and training	4.34	5	4.27	6	4.39	5	4.34	5
F5	High costs of hardware and software	4.43	4	4.47	3	4.41	4	4.43	3
F6	Lack of applicability and practicability regarding the BIM software	3.87	9	3.93	11	4.08	9	3.96	10
F7	Not sure if the benefits outweigh the costs when implementing BIM	4.72	2	4.72	1	4.71	2	4.72	1
F8	Increased workload and decreased efficiency	3.57	10	4.00	9	4.02	12	3.86	11
F9	Lack of standards, laws and regulations	4.26	7	4.18	7	4.22	7	4.22	8
F10	Insufficient information sharing	3.55	11	3.80	12	4.20	8	3.86	11
F11	Insufficient government lead/direction	4.62	3	4.02	8	4.31	6	4.33	6
F12	Resistance to change of culture/thinking mode	4.17	8	4.30	5	4.86	1	4.46	2

Table 5: Response Rate

Stakeholder group	No. of questionnaires		Percentage return
	Sent	Return	
Owner	186	47	25.3%
Designer	178	40	22.5%
Contractor	191	49	25.7%
Total	555	136	24.5%

Table 6: Results of Independent Sample *T*-Tests between Paired Stakeholder Groups for Their Perceptions regarding BIM Adoption Barriers

<i>Paired Stakeholder Groups</i>	<i>Stakeholder perceptions with significant differences</i>	<i>Equal variances assumed</i>	<i>Levene's test for equality of variances</i>		<i>T-test for equality of means</i>				
			<i>F</i>	<i>Sig.</i>	<i>t</i>	<i>df</i>	<i>Sig. (2-tailed)</i>	<i>Mean diff.</i>	<i>Std. error diff.</i>
Owner vs. designer	F1	N	8.925	.004	3.598	69.281	.001	.41968	.11664
	F2	N	19.750	.000	-6.691	72.894	.000	-1.14947	.17180
	F3	Y	.000	.990	2.633	85	.010	.36915	.14022
	F8	N	16.192	.000	-3.652	84.939	.000	-.42553	.11651
	F11	Y	.040	.841	4.626	85	.000	.59202	.12797
Owner vs. contractor	F1	N	8.913	.004	5.258	77.649	.000	.66305	.12609
	F2	N	18.197	.000	-3.621	78.348	.001	-.63569	.17554
	F8	N	5.699	.019	-3.718	93.971	.000	-.44594	.11993
	F10	Y	3.395	.069	-4.913	94	.000	-.65089	.13248
	F11	Y	3.748	.056	2.630	94	.010	.31090	.11822
Designer vs. contractor	F12	N	38.605	.000	-5.182	67.031	.000	-.68693	.13256
	F2	Y	.408	.525	3.939	87	.000	.51378	.13042
	F3	Y	.001	.970	-4.196	87	.000	-.56020	.13350
	F10	Y	.172	.679	-3.017	87	.003	-.40408	.13391
	F12	N	17.376	.000	-4.957	65.780	.000	-.55714	.11239

Note: 2-tailed sig. < 0.05

Table 7: Disparity of Perceptions among the Three Stakeholder Groups

<i>Barriers of BIM adoption in the Chinese AEC industry</i>		<i>Sum of squares</i>	<i>df</i>	<i>Mean square</i>	<i>F</i>	<i>Sig.</i>
F1	Between groups	10.733	2	5.367	13.890	.000
	Within groups	51.385	133	.386		
	Total	62.118	135			
F2	Between groups	28.912	2	14.456	24.009	.000
	Within groups	80.081	133	.602		
	Total	108.993	135			
F3	Between groups	7.025	2	3.512	9.276	.000
	Within groups	50.358	133	.379		
	Total	57.382	135			
F8	Between groups	5.877	2	2.938	9.202	.000
	Within groups	42.469	133	.319		
	Total	48.346	135			
F10	Between groups	10.369	2	5.185	12.319	.000
	Within groups	55.976	133	.421		
	Total	66.346	135			
F11	Between groups	7.621	2	3.810	10.037	.000
	Within groups	50.490	133	.380		
	Total	58.110	135			
F12	Between groups	12.697	2	6.348	15.920	.000
	Within groups	53.038	133	.399		
	Total	65.735	135			

Note: sig.<0.05